

Dynaflux

R1100 V/G Cooling System

Available with Rotary-VANE Pump "V" or Rotary-GEAR Pump "G"

Dynaflux R1100 V/G Cooling Systems, available from Weld Systems Integrators. WSI is a stocking distributor of Dynaflux products, keeping an inventory IN-STOCK at our Warrensville Heights, Ohio location for quick shipment and delivery.

Give us a call today at 844-WSI-WELD or +1-216-475-5629 for available inventory.

Specifications

- Factory set at 50 psi adjustable to 80 psi
- 3 gallon reservoir
- 115 or 230 VAC / 1 ph - 50 / 60 Hz
- 5.6 / 2.8 amp: 60 Hz
- 15,000 BTU
- Dimensions: 23"L x 11"W x 14.75"H
- 1/4" FPT (water in/out) with 5/8" LH standard inert gas fitting
- 8' power cord
- Rugged polyethylene non-dent construction
- Fisible water level through tank
- Thermal overload
- Net weight: 42 lbs / 19 kg
- Foam packed for UPS shipment

R1100 V: Rotary VANE Pump

- 1.7 gpm at 50 psi

R1100 G: Rotary GEAR Pump

- 1.8 gpm at 50 psi
- Built in by-pass to tank



Dynaflux R1100 V/G Cooling System

DYNAFLUX
QUALITY PRODUCTS

© Dynaflux, Inc

R1100 V/G Cooling System is designed for:

EQUIPMENT	UP TO
M.I.G. Guns	750 amps
T.I.G. Torches	750 amps
PLASMA Welders / Cutters	200 amps
RESISTANCE Welders	75 kVA
INDUCTION Welding	5 KW

844-WSI-WELD

www.WSIWeld.com • sales@wsiweld.com