

# DYNAFLUX QUALITY PRODUCTS Model R2000

Water Recirculator: 1.8 GPM | 3 GAL

**IN-STOCK** READY TO SHIP



## Specifications

- Factory set at 50 psi adjustable to 100 psi
- 6 gallon reservoir (15 gallon available)
- 115 or 230 VAC / 1 ph - 50 / 60 Hz  
13.4 / 6.7 amp: 60 Hz
- 230 or 190 VAC / 3 ph - 50 / 60 Hz  
460 or 380 VAC / 3 ph - 50 / 60 Hz  
2.6 / 1.3 amp: 60 Hz 3 ph
- 30,000 BTU
- Dimensions: 23" L x 16" W x 19.5" H
- 1/4" FPT (water in / out) with 5/8" LH standard inert gas fitting
- 8 foot power cord (1 ph only)
- Visible water level / water flow sight glass
- Thermal overload
- Net weight: 68 lbs / 31 kg
- Foam packed for UPS shipment

## R2000: Rotary GEAR Pump (only)

- 3.5 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump  
(Repair Kit Product No. P2001)

R2000 Cooling System is designed for:

EQUIPMENT	UP TO
M.I.G. Guns	1000 amps
T.I.G. Torches	1000 amps
PLASMA Welders / Cutters	300 amps
RESISTANCE Welders	150 kVA
INDUCTION Welding	10 KW

30,000 BTU / HR @ 75° differential between ambient and return water temperature.



**WSI** WELD SYSTEMS INTEGRATORS, INC.  
RESISTANCE WELDING. SOLVED.

DISTRIBUTED BY:

Schaumburg, IL — 847-490-3500

Menomonee Falls, WI — 262-703-0400



Fridley, MN — 763-574-9000

Parkville, MO — 816-777-5999

<https://www.gladwinmachinery.com>